



X.FIBER

The high-resistance composite material



X.FIBER®⁽¹⁾ is a patented composite product, which is truly innovative in the field of laminated shims. This composite material comes in the form of woven fiber sheets, which can be manufactured in several different ways - these fibers can be of the following materials: glass, carbon, aramide, ceramic fibers or a combination of two or more of these different fibers. The sheets are held together by a heat-hardened resin, the resulting material delivers both very high technical performance and excellent peelability. Thus composed, X.FIBER® offers very high levels of technical performance and excellent peelability.

Advantages :

LIGHTNESS

When the demand is for lighter materials, X.FIBER®, as well as INTERCOMPOSITE®⁽³⁾, proves itself by far the lightest of laminated materials (up to eight times lighter than steel or brass!).

Material	Specific weight	Weight-saving	
		X.FIBER-Glass	X.FIBER-Carbon
X.FIBER-Glass	1,37		
X.FIBER-Carbon	1,05		
Steel	8,2	598,54 %	820 %
Brass	8,5	620,44 %	850 %

STRENGTH

Being both lighter and stronger, X.FIBER® can be used to great advantage as a replacement for carbon and stainless steels.

RESISTANCE

X.FIBER® mechanical properties remain unaffected by the rise in temperature. Thus it can be used at temperatures above 572°F (300°C) for the resin and 1.472°F (800°C) as far as fabric is concerned. It is comparable with laminated metals.

(1) X.FIBER® — Trademark registered,

(2) Europe: Patent N° EP 1 444 094 B1,
Canada : Patent N° CA 2 464 337 C,
États-Unis: Patent pending.

(3) INTERCOMPOSITE® — Trademark registered,
France : Patent N° FR 2 572 411 B1.

X.FIBER

The high-resistance composite material

ANTI-FRETTING

X.FIBER® is a total barrier against the galvanic coupling caused by surface contact of different metallic alloys. No further surface treatment is required.

RAPIDITY

The sheets can be peeled by hand, without the need for tools of any kind.

INGENUITY AND ECONOMY

Once they have been peeled, the sheets remain flat and free of deformation. They remain fully re-useable.

Dimensions of X.FIBER® products:

Specific weight		Thickness of laminations (mm / inches)		
X.FIBER-Glass	X.FIBER-Carbon	0,075 .003	0,1 .004	0,11 .0043
1,05				X
1.37		X		
1.39			X	



Sales office: LAMECO USA · 520 Broadway, Suite 350 PMB 140,
Santa Monica, CA 90401 · Ph.: 310 496 4221 · Fax (toll free): 888 317 1055
E-mail: lameco.usa@lamecogroup.com

www.LamecoGroup.com