

МАТЕРИАЛЫ

Слоистые прокладки Lameco



СПЕЦИФИКАЦИЯ / МАТЕРИАЛ						УДЕЛЬНЫЙ ВЕС	ТОЛЩИНА ОТДЕЛЯЕМЫХ СЛОЕВ (ММ/ INCH)											
							СПЕЦИФИКАЦИЯ											
STD	EN	BS	AISI/SAE	UNS	ISO		0,005 .0002	0,010 .0004	0,012 .0005	0,019 .0007	0,023 .0009	0,025 .001	0,05 .002	0,075 .003	0,1 .004	0,11 .0043	0,2 .008	
							1	2	3	4	5	6	7	8	9	10	11	
Алюминий																		
LS1	1200	1200	1200	A91200	AI99,0	2,8							X	X	X			
LS2	5052	5052	5052	A95052	AIMg2,5	2,8							X	X				
Латунь																		
LS3	CuZn37	CZ108		C27700	CuZn37	8,5						X	X	X	X			
Нержавеющая сталь																		
LS4	1.4300	304S31	302	S30200		8,2							X	X	X			
LS5	1.4301	304S15	304	S30400		8,2		X				X	X	X	X			
	1.4350	304S16																
LS6	1.4306	304S11	304L	S30403		8,2							X	X	X			
LS7	1.4401	316S16	316	S31600		8,2						X	X	X				
	1.4436	316S33																
LS8	1.4404	316S12	316L	S31603		8,2							X	X	X			
	1.4435	316S13																
Низкоуглеродистая сталь																		
LS9	1.1121	040A10	1010	G10100	1010	8,2						X	X	X	X			
Титан																		
LS10	3.7025	2TA1	Ti Gr1	R50250	5832-2	4,5						X	X	X	X			
LS11	3.7035	TA 2	Ti Gr2	R50400	5832-2	4,5							X	X	X			
INTERCOMPOSITE*																		
LS12	(полимер / эпоксипласт / полиэфирный пластик)					1,395			X	X	X		X	X	X		X	
DUORPEEL*																		
LS13	(металлизированный полиэстер)					1,395			X	X	X		X					
X.FIBER*																		
LS14	(стеклоткань)					1,37 -> 1,39								X	X			
LS15	(углеродная ткань)					1,05										X		
LS16	(стеклоткань PLUS)					1,35 -> 1,39							X	X	X			
COBRA.X*																		
LS17	(ткань BCRW)					1	X											